



BEFORE

AFTER



TM SMART TRACK SN

TM SMART TRACK SN USES PATENTED, FULLY SYNTHETIC TECHNOLOGY OPTIMIZED FOR APPLICATION THROUGH A SPRAY NOZZLE APPLICATION SYSTEM.

It is pH neutral and is designed for use on plastic chains for the transport of all package types in the food and beverage industries where an anhydrous operation is desired (PET-bottles, cans, cartons, glass etc).

BENEFITS

TM SMART TRACK
DRY LUBRICATION TECHNOLOGY

HYGIENE	Dry environment eliminates the risk of re-infection
SAFETY	Dry floors reduce the danger of injuries.
STRESS CRACK APPROVALS	no bursting of PET bottles – approved by main bottle producers
PACKAGING FRIENDLY	Water free sliding film is easy on cardboard box wrapping.
COST REDUCTION	no water – no waste water
LOW FRICTION	uniform lubrication-film guarantees lower (= better) friction
FOOD GRADE	NSF registered, „LD-50“ approval
IMPROVED LINE EFFICIENCY	ensures a trouble-free operation

APPLICATION

Automatic central dosing system

Specially designed integrated pump and control system applies a very small quantity of TM SMART TRACK SN at specified intervals to the conveyor surfaces through a touchless nozzle delivery system.

Manually

For smaller filling lines TM SMART TRACK SN could be applied by spraying bottle as well (at beginning of shift and then approximately every 4-6 hours).

CLEANING
NOTICE

All conveyors should be cleaned periodically from dust, product residues etc. with a mild foam cleaner.
TM SMART TRACK SN is suitable to only a limited extent for transport of glass bottles on stainless steel conveyors.

24 / 7 POISONING EMERGENCY HOTLINE: + 1 866 706 3262

Appearance	milky yellow or milky white	pH	6.5–7.0
Type of emulsion	O/W	Viscosity (mPa.s)	4–10 mPa.s
Storage temperature	41 °F to 95 °F	Shelf life	12 months



THONHAUSER USA, Inc.
CINCINNATI, OH, 45241
Phone 1 513 771 6263, www.thonhauser.net



US DISTRIBUTOR: AFCO
ALEX C. FERGUSSON, LLC (AFCO) 5000 LETTERKENNY ROAD CHAMBERSBURG, PA 17201
Toll Free 800.345.1329, Fax 717.264.9182, www.afcocare.com